FEATURES AND BENEFITS

- OSB/Replacement Applications
- Deep, forceful threads that will grip into the soft fibers.
- Color matched Powderful™ coating
- ZXL™ is an excellent choice for GALVALUME & other long-life metal roof panels.
- Strip-Loc Thread to Point technology

FOR PROPER INSTALLATION, THE USE OF IMPACT DRIVERS ARE NOT RECOMMENDED FOR POWDER COATED OR ANY WET PAINTED FASTENER

PULLOUT & PULLOVER VALUES ARE DETERMINED IN THE ST FASTENING SYSTEMS ENGINEERING LABORATORY & BASED UPON WOOD DENSITIES FOUND IN PRESENT DAY WOOD PRODUCTS.

TECHNICAL DATA PROVIDED HEREIN IS TO BE USED AS A GUIDE FOR TYPICAL STRENGTH CHARACTERISTICS ONLY.

DUE TO THE INCONSISTENCY OF OSB, THE #12 OSB SCREW WAS DEVELOPED TO REDUCE STRIPOUT TO ENABLE FULL PULLOUT VALUES TO BE OBTAINED.

SIZE	CARTON QTY.	WEIGHT/M
#12 x 1-1/2"	2500	10.1

PULL OUT STRENGTH LBS. ULT.				
SUBSTRATE	PENETRATION	10-16/8 VALUE		
3/4" PLY	3/4"	380		
3/4" PLY	1 1/2"	585		
5/8" PLY	3/4"	453		
5/8" PLY	1 1/2"	588		
1/2" PLY	3/4"	297		
1/2" PLY	1 1/2"	390		
7/16" OSB	3/4"	198		
7/16" OSB	1 1/2"	212		
5/8 OSB	3/4"	361		
5/8 OSB	1 1/2"	441		
2 X SPF	3/4"	378		
2 X SPF	1 1/2"	739		

PULL OVER STRENGTH LBS. ULT.				
SUBSTRATE	GAUGE	THICKNESS	VALUE	
AZ55 Galvalume	29	.015	658	
AZ55 Galvalume	26	.019	927	
AZ55 Galvalume	24	.024	1035	
AZ55 Galvalume	22	.032	1386	

NOTES: 1. *The tabulated value represents the ultimate tensile load at which the ZXL head breaks from the carbon steel fastener body.

2. 1-1/2" Length fully penetrates OSB and Plywood sheeting.

3. 26 and 29 GA values shown were obtained using 80 KSI steel sheeting. 24, 22, and 20 GA values were obtained using KSI minimum steel sheeting.

Wood Binder





HEAD STYLE
HEX
DRILL POINT
SHARP POINT
MAJOR DIAMETER
.215/.210
MINOR DIAMETER
.130/.135

WASHER/HEAD DIAMETER
.500
HEAD ACROSS FLATS

.305/.311

ULT. TENSILE STRENGTH 1575 LBS.

MIN. TORSIONAL STRENGTH 65 IN.-LBS.

NOM. SHEAR STRENGTH 2100 LBS.







ZXL Strip-Loc thread to
Anatomy of the ZXL weather point technology
tight system grips the fiber of OSB

APPLICATIONS











